



Landfill Gas Hose



Serie LFG44

- Temperature Range: -65° to 325° F
- Two-ply silicone poly ester fabric (.44 inch per ply)
- Reinforced with spring 302 stainless steel wire
- Nylon cuff trip over wire
- Bend radius : 1.5" time diameter
- Pressure: -5 PSIG/10 HG Negative
- Pipe size hose ID: 1.55" ID, 1.90" ID, 2.38" ID, 2.88" ID, 3.50" ID, 4.50" ID, 6.62" ID, 8.62" ID, 10.75" ID, and 12.75" ID
- Length : 12" to 48" long or longer for some application .
- Customized ID' are available up to 18"



Tigerflex Serie H, J & K Hose

Standard duty PVC general purpose suction and transfer hose. General application include construction and mining, irrigation line , rock dusting, wellpoint system , agri-foam system , miscellaneous agricultural application and liquid fertilizer transfer. Feature and Benefit of Tigerflex H, J & K Hose:

- PVC construction
- Serie H is clear with white helix
- Serie J is solid olive green
- Serie K is clear with dark green helix
- Smooth bore construction



TigerClamp Spiral Double Bolt Clamp

The TigerClamp™ spiral double bolt clamp are designed to be used with the Tigerflex hose with a convoluted cover (counter-clockwise spiral only). For adequate holding power, a single clamp may be used on each end for 1.5" - 4" ID hose. Two clamps are recommended for each end on 5" ID hose and larger. Made of zinc-plated carbon steel.

