



Landfill Ri er Di connect Adapter

EPG' patented featured Di connect Adapter are de igned to fa ten through a landfill ri er or ump wall. Now per onnel can ea ily and afely make pump connection and/or di connection without entering hazardou location .



"NW" Serie (Stainle Steel)

- Solid 304 Stainle Steel con truction
- In ert and hou ing have tapered lide fitting and O-ring eal , to maximize liquid-tight lip joint ealing
- De igned for maximum ervice life and ea e of maintenance
- Built in 90° elbow with blind top that ha female thread to accept threaded pipe to facilitate ea y removal
- Reduce the need for per onnel to enter hazardou location to make pump connection and/or di connection
- EPDM ga ket for inner and outer wall with a wa her and lock nut to make a ga tight eal
- Extended length di charge allow adapter to fit through 0.25" to 3" material wall thickne
- 1", 1.25", 1.5", 2", and 3" NPT ized fitting for pump, lift-out, and di charge pipe



"N" Serie

- 1/4 the co t of tainle teel
- Electrole nickel plated bra alloy ca ting
- Corro ion re i tant
- High trength
- Teflon coated neoprene O-ring
- Tapered lide/funnel fitting and O-ring feature maximize liquid tight lip joint ealing
- De igned for maximum ervice life and ea e of maintenance
- Feature built in 90° elbow
- Eliminate entrance of per onnel in hazardou location to make pump connection and di connection

