



Industrial Drilling Product



AQF-2™

AQF-2™ foaming agent is an anionic surfactant. AQF-2 foaming agent can be added to fresh water for air/foam, air/gel-foam, or mist drilling application.

AQUA-CLEAR™ AE

AQUA-CLEAR AE is a liquid blend of acid and acid enhancer formulated to control bacterial lime contamination due to the presence of iron related and sulphate reducing bacteria.

AQUA-CLEAR™ MGA

AQUA-CLEAR MGA is a dry blend of granular acid and additive used in the removal of iron, manganese and carbonate scale. It retains strength longer than most liquid acid, which increases its cleaning capability.

AQUA-CLEAR™ PFD

AQUA-CLEAR PFD is a concentrated liquid polymer dispersant that provides superior mud and sediment removal from the producing formation and gravel pack. AQUA-CLEAR PFD contains no phosphate.

AQUAGEL®

AQUAGEL is a finely ground, premium-grade Wyoming sodium bentonite which meets the American Petroleum Institute (API) Specification 13A, Section 4 requirement. AQUAGEL provides viscosity and gelling characteristics to fresh water drilling fluid.

AQUAGEL GOLD SEAL®

AQUAGEL is a finely ground, premium-grade Wyoming sodium bentonite which meets the American Petroleum Institute (API) Specification 13A, Section 4 requirement. AQUAGEL provides viscosity and gelling characteristics to fresh water drilling fluid.

AQUAGUARD™

AQUAGUARD is a single-pack grout containing granular Wyoming sodium bentonite blended with inorganic additive. The grout is designed for sealing the annular space around monitor or water well casing.

BARAFOS®

BARAFOS, a non-glassy, modified polyphosphate, is used as a thinner and dispersant in fresh water drilling fluid and as an aid in water well development.