



Type 21 Ball Valve

Standard Feature (Size 1/2" – 6")

- Pressure rated up to 230 psi (PVC, CPVC, PVDF)
- Double O-ring seal on stem for an added protection.
- Full bore, size 1/2" – 2"
- Full vacuum rated, all size
- Block in two direction, up stream and down stream, leaving full pressure on the opposite end of the valve
- Integrally molded ISO mounting pad for both manual and actuated operation
- Integrally molded base pad to mount valve. Securely on panel mounting
- PTFE seat with elastomeric backing cushion ensure bubble-tight shut-off and a low fixed torque, while at the same time compensating for wear
- True Union design for easier installation or repair without expanding the pipe system
- Built-in spanner wrench on the handle for valve disassembly and assembly
- Two set of end connector (socket and threaded) included with all PVC and CPVC valve in size 1/2"– 2"
- CPVC threaded end connector on size 1/2" – 1" come with stainless steel reinforcing ring



Option

- Pneumatic and electric actuator & accessories
- Stem extension
- 2" square operating nut or "T" nut
- Locking and/or spring return handle
- Limit switches



Multiport Ball Valve

Standard Feature (Size 1/2" – 6")

- True Union design on all three port
- Blow-out proof, solid mold bottom entry design
- Block from left or right union port, leaving full pressure on the opposite end of valve
- Standard "L" port ball permit flow from common port to either left or right port or to "OFF" position
- All size rated for full vacuum service
- Eliminate need for additional valve and "Tee"

Option

- Pneumatic and electric actuator & accessories
- Stem extension
- 2" square operating nut or "T" nut
- Locking handle
- Limit switches
- "T" port
- Double "L" port