



Socket Coupling

Produced to ASTM D2513 and D2683

| <u>Socket Coupling</u> | <u>Dimensions G x E (in)</u> | <u>Package Weight (lbs.)</u> | <u>CSA</u> | <u>IAPMO</u> |
|------------------------|------------------------------|------------------------------|------------|--------------|
| 1/2" CTS | 2.30 x 1.07 | 0.5 | x | x |
| 3/4" CTS | 2.10 x 1.27 | 0.5 | x | |
| 1" CTS | 1.95 x 1.52 | 0.7 | x | |
| 1 1/4" CTS | 1.54 x 1.80 | 0.6 | x | |
| 1/2" IPS | 2.10 x 1.27 | 0.5 | x | |
| 3/4" IPS | 1.95 x 1.46 | 1.0 | x | x |
| 1" IPS | 1.54 x 1.80 | 0.7 | x | x |
| 1 1/4" IPS | 2.08 x 2.32 | 1.6 | x | x |
| 1 1/2" IPS | 2.33 x 2.65 | 2.2 | x | x |
| 2" IPS | 2.36 x 3.31 | 3.6 | x | x |
| 3" IPS | 2.85 x 4.88 | 9.2 | x | x |
| 4" IPS | 3.11 x 6.30 | 17.6 | x | x |