


Requires 0.8 or 1.0 XL or XXL Brass Cutter and Black Cap

**Standard Water Tapping Tee*
Flat Gasket
Butt Outlet
extended chimney regular base**

Main Size (Nominal) (IPS / DIPS)	Outlet Size	Butt Outlet DR/Wall	Dimension A (in)	Package Weight for Ext. Chimney (lbs.)	
				With Sleeve	Without Sleeve
1 1/4-16"	3/4" CTS	0.090	1.97"	10.3	3.9
	1" CTS	0.090	2.48"	10.1	3.8
		0.102		10.3	3.9
		0.125		10.4	3.9
1 1/4-16"	3/4" IPS	DR 11	2.44"	10.7	3.8
	1" IPS	DR 9	2.70"	10.8	3.9
		DR 11		10.7	3.8
	1 1/4" IPS	DR 9	2.25"	12.7	4.2
		DR 11		12.5	4.0

*DriscoPlex™ tapping tees and cutters are designed and intended to tap polyethylene mains of wall thickness as defined in PP32.3. Special precautions are necessary when working in gaseous environments or elevated temperatures. Consult your Operations and Safety Manuals for specific recommendations. The use of these tapping tees and cutters beyond this scope is at the user's own risk.



**High Volume Water Tapping Tee* O-Ring Seal
Butt/Outlet**

**Extended Chimney Rectangular Base
Standard - brass cutters and black cap**

Main Size (Nominal) (IPS / DIPS)	Outlet Size	Butt Outlet DR/Wall	Dimension L (in)	Package Weight for Ext. Chimney (lbs.)	
				With Sleeve	Without Sleeve
2 - 16"	1 1/4" CTS	0.121	5.9"	35.2	25.2
	1 1/4" IPS (Butt)	DR 9	5.3"	35.2	25.2
		DR 11		35.2	25.2
	2" IPS (Butt)	DR 9	5.3"	36.6	25.6
		DR 11		34.6	24.6

*DriscoPlex™ tapping tees and cutters are designed and intended to tap polyethylene mains of wall thickness as defined in PP32.3. Special precautions are necessary when working in gaseous environments or elevated temperatures. Consult your Operations and Safety Manuals for specific recommendations. The use of these tapping tees and cutters beyond this scope is at the user's own risk.